

OMEGA Tiles



Caractéristiques	Technische Daten	Technical details	
Mode de fabrication	Herstellungsart	Manufacturing method	Needlepunch
Aspect	Art des Flors	Pile type	Dilours
Type de teinture	Art der Färbung	Dyeing method	Solution Dyed
Surface	Polmaterial	Pile content	100 % Polypropylene
Dossier	Rücken	Backing	Bitumen Backing
Poids du velours	Poleinsatzgewicht	Pile weight	ca 900 gr/m ²
Hauteur du velours	Polhöhe	Pile height	ca 6 mm
Epaisseur totale	Gesamtdicke	Total Thickness	ca. 7,5 mm
Poids total	Gesamtgewicht	Total weight	ca 4000 gr/m ²
Largeur	Lieferbreite	Width	500 x 500 mm
Classement feu	Brennverhalten	Flammability classification	Cfl S1 acc. to EN 13501-1
Classement antistatique	Antistatisches Verhalten	Electrostatic properties	Walking Test < 2,0 KV Resistance ≥ 10 ¹⁰
Domaine d'usage	Einsatzbereich	Suitability	EN1307 - 31 - Commercial Moderate
Isolation phonique	Trittschalldämmung	Impact Sound Insulation	27dB - ISO 10140-1
Solidité des coloris :	Farbechtheit :	Colour fastness :	
Lumière (dedans)	Lichtecheit (Innen)	To light (Inside)	5 according to ISO 105-B02
Frottement sec	Reibecheit trocken	To rubbing dry	5 according to ISO 105-X12
Frottement humide	Reibecheit nass	To rubbing wet	4 according to ISO 105-X12
Resistance au chlor	Chlorecheit	Bleach resistance	Yes

Maintenance

The fibre blend used has exceptional resistance to soiling and facilitates the use of recognised cleaning solutions.

This carpet must be sold and installed in accordance with BS5325. Chair mats are recommended for use under castor chairs.

All specifications are subject to normal commercial tolerances and subject to change where they improve the product's performance.

Pile reversal / shading

Carpets may be subject to permanent pile reversal, also known as "shading" or "watermarking". The pile in certain areas may become distorted, giving the appearance of areas of light and shade. No specific cause of this has been identified and it is no manufacturing fault.

We reserve the right to make technical alterations and improvements to this product. Colour variations from the original sample can occur.

